






Starlock® Push-On Fasteners Flangeless Type



A		B	C	
Shaft Size	Part No:	Outside Diameter	Material Thickness	Style
2.00mm	7115	20.00mm	0.4mm	X
3.00mm	8168	9.70mm	0.2mm	Y
3.00mm	8121	36.56mm	0.254mm	W
4.00mm	8120	16.00mm	0.35mm	Y
3/16"	7039	.395"	.008"	Y
3/16"	8122	1.440"	.010"	W
.190"	7128	.650"	.010"	Y
.190"	7188	.875"	.008"	Y
5.00mm	8105	9.60mm	0.254mm	Y
7/32"	7223	.600"	.010"	Y
6.00mm	8106	10.50mm	0.4mm	Y
6.00mm	8123	36.58mm	0.376mm	W
6.10mm	8173	22.23mm	0.2mm	Y
1/4"	6834	.475"	.014"	Y
1/4"	7225	.812"	.008"	V
7.00mm	8050	12.07mm	0.35mm	Y
9/32"	8055	.472"	.014"	Y
9/32"	8020	.812"	.008"	V
9/32"	7226	1.094"	.012"	V
5/16"	6835	.565"	.010"	Y
5/16"	7183	.740"	.016"	Y
11/32"	7224	1.093"	.012"	Y
10.00mm	8071	27.76mm	0.3mm	Y
13/32"	8011	1.093"	.012"	Y
.417"	7076	1.000"	.024"	Y
7/16"	7106	.800"	.024"	Z
7/16"	8012	1.093"	.012"	Y
13.00mm	8134	20.75mm	0.305mm	Z
13.00mm	8013	27.76mm	0.305mm	Y
14.00mm	8148	22.225mm	0.6mm	Z
14.00mm	7107	24.10mm	0.6mm	Z
9/16"	7221	.950"	.024"	Z



Where a greater degree of flexibility is required compared with a standard Starlock® Push-on Fastener, or where there is insufficient room for the flange, a flangeless fastener can be used. With certain fasteners assembly is possible without the use of a tool. This is a particularly attractive feature in the soft toy industry for the mounting of items such as eyes and noses. The ribbed style is used to hold insulation in place as large diameter eliminates damage.

All dimensions shown are subject to engineering tolerances
 These fasteners can be supplied in blue and varnish finish for imperial BV sizes, in bronze and varnish finish for metric BV sizes or in mechanical zinc plated DT finishes.
 Starlocks® are generally in spring steel and many are also supplied in stainless steel
 Non-standards parts may be subject to a minimum order quantity

